40V N-Channel Trench Power MOSFET

General Description

The SJD45N130 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 4.5V. This device is suitable for use as a wide variety of applications.

Features

- Low Gate Charge
- 100% UIS Tested, 100% DVDS Tested
- High Power and current handing capability
- Lead free product is acquired

Application

- DC/DC Converter
- Ideal for high-frequency switching and synchronous rectification

Key Performance Parametes

Parameter	Value	Unit
V_{DS}	45	V
$R_{DS(ON)_TYP}$	12.3	mΩ
I_D	36	A
Q_G	21	nC



Schematic Diagram



TO-252(DPAK) top view

RoHS

Package Marking and Ordering Information

Device/Ordering Code	Marking	Package	Packing	Reel Size	Tape width	Quantity
SJD45N130	SJD45N130	TO-252	Tape	\	\	2500 Pcs

Table 1. Absolute Maximum Ratings (T_C=25℃ unless otherwise noted)

Symbol	Parameter	Limit	Unit
V_{DS}	Drain-Source Voltage (V_{GS}=0V)	45	V
V_{GS}	Gate-Source Voltage (V_{DS}=0V)	±20	V
I_D	Drain Current-Continuous(T_C=25℃)	36	A
	Drain Current-Continuous(T_C=100℃)	23	A
$I_{DM\ (pluse)}$	Drain Current-Continuous@ Current-Pulsed (Note 1)	144	A
P_D	Maximum Power Dissipation(T_C=25℃)	34	W
	Maximum Power Dissipation(T_C=100℃)	13.5	W
E_{AS}	Avalanche energy (Note 2)	56	mJ
T_J, T_{STG}	Operating Junction and Storage Temperature Range	-55 To 150	℃

Table 2. Thermal Characteristic

Symbol	Parameter	Typ	Max	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case		3.7	℃/W

Table 3. Electrical Characteristics (T_J=25℃ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
On/Off States						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V I_D=250μA	45			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=45V, V_{GS}=0V T_J=25℃			1	μA
		V_{DS}=45V, V_{GS}=0V T_J=125℃			100	μA
I_{GSS}	Gate-Body Leakage Current	V_{GS}=±20V, V_{DS}=0V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=250μA	1		2.5	V
g_{FS}	Forward Transconductance	V_{DS}=5V, I_D=15A		22		S
$R_{DS(ON)}$	Drain-Source On-State Resistance	V_{GS}=10V, I_D=15A T_J=25℃		12.3	15.4	mΩ
		V_{GS}=4.5V, I_D=10A T_J=25℃		15	20	mΩ
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS}=20V,V_{GS}=0V, f=1.0MHz		1130		pF
C_{oss}	Output Capacitance			79		pF
C_{rss}	Reverse Transfer Capacitance			67		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1.0MHz		1.6		Ω
Switching Parameters						
$t_{d(on)}$	Turn-on Delay Time	V_{GS}=10V, V_{DS}=22V, R_L=1.5Ω, R_{GEN}=3Ω		9.4		nS
t_r	Turn-on Rise Time			7.2		nS
$t_{d(off)}$	Turn-Off Delay Time			30.2		nS
t_f	Turn-Off Fall Time			5.8		nS
Q_g	Total Gate Charge	V_{GS}=10V, V_{DS}=22V, I_D=15A		21		nC
Q_{gs}	Gate-Source Charge			3.5		nC
Q_{gd}	Gate-Drain Charge			3.8		nC
Source-Drain Diode Characteristics						
I_{SD}	Source-Drain Current (Body Diode)				36	A
V_{SD}	Forward on Voltage (Note 3)	V_{GS}=0V, I_S=15A			1.2	V
t_{rr}	Reverse Recovery Time	I_F=15A, dI/dt=100A/μs		18.3		ns
Q_{rr}	Reverse Recovery Charge	I_F=15A, dI/dt=100A/μs		6.8		nC

Notes 1.Repetitive Rating: Pulse width limited by maximum junction temperature.
Notes 2.E_{AS} condition: T_J=25℃,V_{DD}=40V,V_G=10V, Rg=25Ω, L=0.5mH.
Notes 3.Repetitive Rating: Pulse width limited by maximum junction temperature.

Typical Electrical And Thermal Characteristics (Curves)

Figure 1. Output Characteristics



Figure 2. Transfer Characteristics



Figure 3. Power Dissipation



Figure 4. Drain Current



Figure 5. BV_{DSS} vs Junction Temperature



Figure 6. $R_{DS(ON)}$ vs Junction Temperature



Typical Electrical And Thermal Characteristics (Curves)

Figure 7. Gate Charge Waveforms



Figure 8. Capacitance



Figure 9. Body-Diode Characteristics



Figure 10. Maximum Safe Operating Area



TO-252 Package Information



Symbol	Dimensions In Millimeters		
	Min.	Typ.	Max.
A	2.200	2.300	2.400
A1	0.000		0.127
b	0.640	0.690	0.740
c(电镀后)	0.460	0.520	0.580
D	6.500	6.600	6.700
D1	5.334 REF		
D2	4.826 REF		
D3	3.166 REF		
E	6.000	6.100	6.200
e	2.286 TYP		
h	0.000	0.100	0.200
L	9.900	10.100	10.300
L1	2.888 REF		
L2	1.400	1.550	1.700
L3	1.600 REF		
L4	0.600	0.800	1.000
Φ	1.100	1.200	1.300
θ	0°		8°
θ1	9° TYP		
θ2	9° TYP		

Attention

This product described in this document can not be used in life support devices or systems, aircraft's control systems, and other applications whose failure can be reasonably expected to result in serious physical and/or material damage，apart from that when an application agreement is signed between customer and Wuxi Shangjia Semiconductor.

The performances and characteristics of this product in the independent testing state are displayed in this document. Wuxi Shangjia Semiconductor can't guarantee of the performances and characteristics of this described product that mounted in the customer's products or equipments as same as that in the independent testing state. So the customer should evaluate and test devices mounted in the customer's products or equipments.

Wuxi Shangjia Semiconductor reserves the right to improve the designs, functions and reliability of this product and modify any and all information described in this document without notice customer, apart from that when an notice agreement is signed between customer and Wuxi Shangjia Semiconductor.

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Wuxi Shangjia Semiconductor hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.